

RC MOWERS

Remote Control Robotic Slope Mowers

PRODUCT SPECIFICATIONS



	TK-60XP	TK-52XP	TK-48P	TK-44E	72XP	60XP
ENGINE	KAWASAKI® FX1000V AIR-COOLED HEAVY-DUTY AIR CLEANER	KAWASAKI® FX850V AIR-COOLED HEAVY-DUTY AIR CLEANER	KAWASAKI® FX691V AIR-COOLED HEAVY-DUTY AIR CLEANER	KAWASAKI® FR651V AIR-COOLED	KAWASAKI® FX921V AIR-COOLED HEAVY-DUTY AIR CLEANER	KAWASAKI® FX850V AIR-COOLED HEAVY-DUTY AIR CLEANER
HORSEPOWER	35	27	22	21.5	31	27
DISPLACEMENT	999 CC	852 CC	726 CC	726 CC	999 CC	824 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-5400 TRANSAXLES	HYDRO-GEAR® ZT-5400 TRANSAXLES	HYDRO-GEAR® ZT-3400 TRANSAXLES	HYDRO-GEAR® ZT-3100 TRANSAXLES	HYDRO-GEAR® ZT-5400 TRANSAXLES	HYDRO-GEAR® ZT-5400 TRANSAXLES
FUEL CAPACITY GAL	13.4	13.4	10	5	13.4	13.4
GROUND SPEED (Approx. Mph)	5.3	5.3	3.9	3.1	7.0	7.0
ACRES PER HOUR	2.5	2.2	1.7	1.2	4.0	3.3
SLOPE CLIMB ABILITY DEGREES	50	50	45	45	35	35
DECK						
DECK CONSTRUCTION	FABRICATED 7 GA. STEEL With 1/4 IN. SPINDLE REINFORCEMENT	FABRICATED 7 GA. STEEL With 1/4 IN. SPINDLE REINFORCEMENT	FABRICATED 7 GA. STEEL With 1/4 IN. SPINDLE REINFORCEMENT	FABRICATED 7 GA. STEEL With 1/4 IN. SPINDLE REINFORCEMENT	FABRICATED 7 GA. STEEL With 1/4 IN. SPINDLE REINFORCEMENT	FABRICATED 7 GA. STEEL With 1/4 IN. SPINDLE REINFORCEMENT
NUMBER OF SPINDLES	3	3	3	3	3	3
DECK ENGAGEMENT	OGURA® ELECTRIC CLUTCH	OGURA® ELECTRIC CLUTCH	OGURA® ELECTRIC CLUTCH	OGURA® ELECTRIC CLUTCH	OGURA® ELECTRIC CLUTCH	OGURA® ELECTRIC CLUTCH
CUTTING WIDTH - IN	60	52	48	44	72	60
CUTTING HEIGHTS - IN	2.5 ~ 6.5	2.5 ~ 6.5	2.5 ~ 6.5	2.5 ~ 6.5	1.0 ~ 5.5	1.5 ~ 5.5
TRACKS/WHEELS						
TRACK CONSTRUCTION	RUBBER MOLDED OVER STEEL LINKS, WITH STEEL CORDS	RUBBER MOLDED OVER STEEL LINKS, WITH STEEL CORDS	RUBBER MOLDED OVER STEEL LINKS, WITH STEEL CORDS	RUBBER MOLDED OVER STEEL LINKS, WITH STEEL CORDS	4 PLY	4 PLY
TRACK SIZE	9IN WIDE 230mm x 72mm x 44mm TREAD STYLE 'J'	9IN WIDE 230mm x 72mm x 44mm TREAD STYLE 'J'	7 IN WIDE 180mm x 72mm x 39mm TREAD STYLE 'WAVE'	7 IN WIDE 180mm x 72mm x 39mm TREAD STYLE 'WAVE'	(REAR) RADIAL TURF 24X12-12 (FRONT) SMOOTH 15 X 6-6 SEMI PNEUMATIC	(REAR) RADIAL TURF 24X12-12 (FRONT) SMOOTH 15 X 6-6 SEMI PNEUMATIC
DIMENSIONS						
WEIGHT - LBS	1856	1790	1520	1218	1523	1334
LENGTH - IN	93	93	86	82	80	80
WIDTH - IN	86	78	69.5	63	75	69
HEIGHT - IN	49.5	49.5	48.5	34	47.8	47.8
WARRANTY	2 YEAR / 400 HOURS	2 YEAR / 400 HOURS	2 YEAR / 400 HOURS	1 YEAR / 200 HOURS	2 YEAR / 400 HOURS	2 YEAR / 400 HOURS