



616-863-9155 | [equipment@amplirollusa.com](mailto:equipment@amplirollusa.com) | [amplirollusa.com](http://amplirollusa.com)

**35,000  
POUNDS**



## WHY BUY A HOOKLIFT?

Do you have trucks that are not always being used?

Do you have a difficult time finding quality drivers?

Is there a piece of equipment you could use, but can't justify adding another truck?

**It's Multi-tasking for your truck.  
The possibilities are Infinite.**

## DELIVER | LOAD | DUMP

The **Ampliroll Hooklift** was invented in 1969. Our process of laser cutting and robotic welding enables us to provide you with a complete line of hooklifts, that eliminate the use of SHIMS and WEAR PADS.



## FEATURES:

- **Sliding Jib** gives you greater range of body lengths and optimal weight distribution.
- **Twin Pivot** allows you to dump a uniform pile of material.
- **Dual Cylinders** gives greater stability while dumping and loading.
- **Safely operated** from the drivers seat.
- **Dock Level** loading and unloading
- **Double your payload** by pulling another body on a trailer.
- **Maneuverable** to operate, the container can be loaded within a 60 degree arc.
- **Spot** the container exactly where you want it, by pushing it into place with no damage.
- **Quickly loads** a body in less than one minute.
- **Investment** that will outlast your truck, Amplirolls® will last over 25 years.
- **Meets** all highway safety standards.

	AMP 140-165-15	AMP 140-181-17	AMP 140-197-18	AMP 140-220-20
<b>LIFTING CAPACITY</b> (including container)	35,000 lbs.	35,000 lbs.	35,000 lbs.	35,000 lbs.
<b>SHIPPING WEIGHT</b>	4510 lbs.	4510 lbs.	4686 lbs.	4994 lbs.
<b>DUMP ANGLE</b>	52°	58°	58°	58°
<b>CAB TO TRUNNION*</b>	126" - 151"	138" - 164"	154" - 186"	178" - 204"
<b>OVER ALL LENGTH</b> From Hook**	175"	190"	206"	230"
<b>BODY LENGTH</b>	12' - 18'	13' - 19'	13' - 20'	15' - 22'

#### HOOK HEIGHT

##### Standard

61 3/4"

##### Optional

54" or MA 54" - 61 3/4"

#### HYDRAULIC SPECIFICATIONS:

##### Pump

Axial piston, 5,700 psi, 14 GPM @ 1,200  
Standard - DIN Shaft or optional SAE 7/8th Shaft

##### Controls

Low pressure hydraulic, cable or air in cab

##### Reservoir

12 gallons

##### Filter

10 micron, return line with replaceable cartridge

##### Maximum operating pressure

4,800 psi

##### Hoses, tubes & fittings

all JIC/SAE specifications

#### STEEL: SPECIAL ALLOY

##### ASTM A 572

in jib, central arm and tilting frame

#### SAFETY DEVICES:

##### Safety valve

prevents jib operation during dump mode

##### Counter-balance valve

to hold cylinder if hose breaks

##### Automatic locking device

for dump mode

##### Slide through container locks

#### TRUCK REQUIREMENTS:

##### GVWR

45,000 to 60,000 lbs

##### Front Axle Capacity

14,000 to 18,000 lbs

##### Rear Axles Capacity

32,000 to 44,000 lbs

#### NOTICE:

Longer containers may not comply with I.C.C. bumper regulations and can effect dump angle.

\*Need to confirm CA or CT with factory or local dealer for proper installation.

\*\*Some subframes are longer, check with local dealer.



4750 14 Mile Road NE | Rockford, MI 49341

Phone: 616-863-9155

Fax: 616-863-9177

Toll Free: 866-822-3580

equipment@amplirollusa.com

amplirollusa.com

Distributed by:

