



AMPLIROLL®

HOOKLIFT SYSTEMS

ONE TRUCK. INFINITE POSSIBILITIES.

Easy to Operate - from inside the truck.

Maneuverable - up to 60 degrees.

Versatile - you can have any attachment you need for a job.

Safety - ground level loading.

Efficient - no need for workers to wait on the truck.

Savings - fewer trucks means less operating costs.



MARREL

CORPORATION

4750 14 Mile Road NE | Rockford, MI 49341

Phone: 616-863-9155 | Fax: 616-863-9177

Toll Free: 866-822-3580

equipment@amplirollusa.com

amplirollusa.com

LIFTING CAPACITY	MODEL	SHIPPING WEIGHT	DUMP ANGLE	CAB TO AXLE*	LENGTH FROM HOOK	BODY LENGTH	HOOK HEIGHT (Standard/Optional)
13,000 lbs	AL 90S-12	1790 lbs.	58°	84" - 108"	124"	9' - 13.5'	36" / 54" (Reduces capacity to 10,000 lbs.)
	AL 90L-14	1790 lbs.	61°	108" - 126"	144"	10' - 14'	
18,000 lbs	AL 95SS-12	2408 lbs.	54°	96" - 120"	146"	10' - 13'	
	AMP 95SS-12	2408 lbs.	58°	96" - 120"	146"	11' - 13'	54" /
	AL 95S-15	2408 lbs.	54°	120" - 138"	162"	10' - 16'	36" or
	AMP 95S-15	2408 lbs.	60°	120" - 138"	162"	13' - 16'	MA 36"-54" / TEL
	AL 95L-16	2417 lbs.	54°	126" - 150"	174"	11' - 17.5'	36"-54"
	AMP 95L-16	2408 lbs.	60°	126" - 150"	174"	14' - 17.5'	
20,000 lbs.	AMP 100SS-12	2408 lbs	58°	96" - 120"	144"	10' - 13'	
	AL 100SS-12	2408 lbs	54°	96" - 120"	146"	10' - 13'	54" /
	AMP 100S-15	2408 lbs	60°	120" - 138"	160"	11' - 16'	
	AL 100S-15	2408 lbs	54°	120" - 138"	162"	10' - 16'	36" or
	AMP 100L-16	2417 lbs	60°	126" - 150"	172"	11' - 17.5'	MA 36"-54" / TEL
	AL 100L-16	2417 lbs	54°	126" - 150"	174"	11' - 17.5'	36"-54"
26,000 lbs.	AL 120SS-10	3307 lbs.	52°	96" - 108"	127"	9' - 12'	54" /
	AL 120SS-12	3307 lbs.	52°	102" - 110"	137"	9' - 14'	
	AL 120S-14	3307 lbs.	53°	120" - 138"	156"	11' - 16'	36" or
	AL 120L-16	3450 lbs.	60°	138" - 156"	178"	12' - 17.5'	MA 36"-54" / TEL
31,000 lbs.	AMP 140-183-16	4260 lbs.	58°	158" - 180"	192"	13' - 18'	61 3/4" /
	AMP 140-189-18	4260 lbs.	58°	170" - 192"	200"	13' - 20'	54" or MA 54" - 61 3/4"
35,000 lbs.	AMP 140-165-15	4510 lbs	52°	126" - 151"	175"	12' - 18'	
	AMP 140-181-17	4510 lbs	58°	138" - 164"	190"	13' - 19'	61 3/4" /
	AMP 140-197-18	4686 lbs.	58°	154" - 186"	206"	13' - 20'	54" or
	AMP 140-220-20	4994 lbs.	58°	178" - 204"	230"	15' - 22'	MA 54" - 61 3/4"
40,000 lbs.	AMP 150-165-15	4510 lbs.	52°	126" - 151"	177"	12' - 18'	
	AMP 150-181-17	4510 lbs.	58°	138" - 164"	190"	13' - 19'	61 3/4" /
	AMP 150-197-18	4686 lbs.	58°	154" - 186"	206"	13' - 20'	54" or
	AMP 150-220-20	4994 lbs.	58°	178" - 204"	230"	15' - 22'	MA 54" - 61"
50,000 lbs.	AMP 160-212-20	5565 lbs.	58°	174" - 190"	222"	15' - 22'	
	AMP 160-232-22	5730 lbs.	58°	186" - 210"	242"	16' - 24'	61 3/4" / 54" or MA 54" - 61 3/4"
60,000 - 65,000 lbs.	AMP 160-185-17	5148 lbs.	56°	138" - 168"	194"	12' - 19'	
	AL 160/2000-22	7030 lbs.	57°	186" - 200"	233"	16' - 24'	61 3/4"