

Xtreme VAC

by 



DCL800TM

- Kubota 4-cylinder
gasoline engine rated 87HP
- 28" suction impeller
 - Hydraulic hose boom
 - Tandem rubber Torflex axles
 - 16" dia. x 100" rubber intake hose

The DCL800TM has the best suction of any unit in it's class. Contact your local Xtreme Vac dealer to order yours today!

*Standard color is white.

*Units may be shown with options.



Sold and Serviced by:



Call: 1-800-362-0240
Email: sales@mtechcompany.com



Scan using your phone's camera



Sourcewell
Formerly NJPA

Awarded Contract

Contract # 041217-ODB



Specifications

Self-Contained Debris Collector-Trailer Mounted

Engine - Gas

Kubota WSG3800 3.8L 4-cylinder gasoline engine, rated at 87HP, meets EPA T2 & CARB T3 standards.

Engine Controls

Electronic engine controls with safety shut down.

Drive

Belt driven via a 4-groove power band.

Hoist

Gear driven hydraulic pump powers 15.2 ton capacity underbody hoist that dumps to 52 degrees.

Hopper

Container constructed of 11 gauge steel with vented top and side hinge rear doors. Available in 14, 20, 25 & 30 cu.yd. capacities.

Axles

14CY - Dual 3.5" Torflex axles rated at 16,000 lbs.
20CY - Dual 5" Torflex axles rated at 20,000 lbs.
25/30CY-Dual 5" Torflex axles rated at 24,000 lbs.
Equipped w/ electric brakes with break-away actuator.

Tires

14CY - (4) ST235-85R16 radial tires on steel wheels.
20/25/30CY - (8) 235/80R16E tires on steel wheels.

Options

- 3-axis hose boom (up/dn, left/rt, in/out)
- Hydraulic parking jack in lieu of manual
- Fluid drive coupler in lieu of standard clutch
- Remote electric throttle for engine
- Urethane suction hose in lieu of rubber
- Urethane coated liners for blower housing
- Driver's side (street) pick up
- Perforated top screens with 3/16" holes
- Air Scoop or Bottom Exhaust on box
- Rotary self-cleaning radiator screen

Engine - Option

John Deere 4045TFC03 4-cylinder diesel engine rated at 74HP - Final T4

Radiator Screen

Boxed corrugated radiator screen constructed from perforated steel to increase air flow for better cooling.

PTO

13" clutch assembly with 2.25" PTO shaft and safety engagement system.

Hose Boom

Hydraulic hose boom powered by 12v electric / hydraulic pump.

Hose

16" x 100" rubber suction hose with steel nozzle.

Impeller

28" dia. suction impeller with six 3/8" thick T-1 abrasive resistant steel blades. Replaceable 1/4" thick steel liners.

Fuel Tank

40-gallon polyethylene fuel tank.

Pintle Eye

Heavy-duty height adjustable pintle eye with three quick release pins.

Parking Jack

Manual parking jack with drop foot.

Lights

LED type DOT trailer lights. Two amber LED flashers in the rear.

Paint

All components are pre-painted with PPG paint - Hopper - standard white, other custom paint colors available as options.



*Units may be shown with options.

