

KÄRCHER

POWER FOR EVERYTHING YOU PLAN TO DO

The Holder S 75 -
powerful and pavement-friendly



HOLDER S 75



Engine

	Deutz TCD 3.6 4-cylinder common rail turbodiesel
Power	75 HP (55.4 kW)
Max. torque at 1300 rpm	410 Nm
Cubic capacity	3,621 cm ³
Emission standard	Stage V/Tier 4 Final, exhaust gas treatment with DOC/DPF, no SCR (DEF)
Fuel tank	22 gal (84 l)

Drive

	Infinitely variable DUAL DRIVE traction drive system (combination of hydrostatic and mechanical drive) with permanent all-wheel drive and electronic load limit control
Speed	Driving speeds 0-25 mph (0-40 km/h) (fast gear)/ 0-25 mph (0-20 km/h) (slow gear); working speed 0-9 mph (0-15 km/h) (fast gear)/ 0-5 mph (0-8 km/h) (slow gear)
Differential lock	Front and rear mechanical with 100% locking effect
Service brake	Hydraulically activated wet disc brakes, active on all four wheels
Parking brake	Electric parking brake, active on both axles

Front PTO shaft

Speed	Switchable from 540 to 1,000 rpm at 1,700 rpm engine speed
-------	--

Hydraulics

Tandem pump volume flow	2 × 19 cm ³ /rev or 11 gpm (43.5 l/min) at 2611 psi (180 bar), of which 0-25 mph (0-40 l/min) for implements, can be controlled from the cab, supply and return at the front and rear (optional), circuit independent of steering and lifting functions
Volume flow of implement variable displacement pump	0-32 gpm (0-120 l/min) at 4061 psi (280 bar), of which 0-26 gpm (0-100 l/min) for implements, can be controlled from the cab, supply and return at the front and rear (optional)
Hydraulic control units	Up to 4 double-acting control units
Hydraulic couplings	Up to 3 pairs of couplings at the front/up to 1 pair of couplings at the rear
Hydraulic tank	9 gal (34 l) with fill level sensor
Front power lift	CAT II, double-acting, with floating position and vibration damping system, optional electro-hydraulic implement release, hydraulic side and incline adjustment
Lifting force	5952 lb (2,700 kg)

Weight

	Includes driver of 165 lb (75 kg); depending on tire size and equipment
Unladen weight	6834 lb (3,100 kg)
Total permissible weight	12125 lb (5,500 kg)
Permissible axle load	Front: 7054 lb (3,200 kg) Rear: 7054 lb (3,200 kg)
Towing capacity	Unbraked: 5511 lb (2,500 kg) Overrun braked: 9920 lb (4,500 kg)

Dimensions

	Depending on tires/dimensions with wheel 280/80R18
Wheelbase	72" (1,827 mm)
Total length incl. front power lift	147" (3,750 mm)
Total height	89" (2,270 mm)
Total outer width	51" (1,310 mm)
Turning circle radius outside	275" (7,000 mm)

Kärcher Municipal North America

Phone: 844. 332. 3200 | Fax: 613. 443. 9600

sales-na@municipal.kaercher.com | www.kaerchermunicipal-na.com