

Xtreme Vac

by 



LCT450

- Kubota WSG3800 3.8L 4-cylinder gasoline engine rated 87HP, EPA T2
- 28" suction impeller
- Hydraulic hose boom
- 16" dia. x 120" rubber intake hose

The LCT450 has the best suction of any unit in it's class. Contact your local Xtreme Vac dealer to order yours today!

*Standard color is white.

*Units may be shown with options.



Sourcewell
Formerly NJPA
Awarded Contract
Contract # 041217-ODD



Sold and Serviced by:



Call: 1-800-362-0240
Email: sales@mtechcompany.com



Scan using your phone's camera

Specifications

Tow-Behind Debris Collector-Trailer Mounted

Engine - Gas

Kubota WSG3800 3.8L 4-cylinder gasoline engine, rated at 87HP, meets EPA T2 & CARB T3 standards.

Engine Controls

Electronic engine controls with safety shut down.

Drive

Belt driven via a 3-groove power band.

PTO

13" clutch assembly with 2.25" PTO shaft and safety engagement system.

Impeller

28" dia. suction impeller with six 3/8" thick T-1 AR steel plate blades. Replaceable 1/4" thick steel liners.

Pintle Eye

Heavy-duty height adjustable pintle eye with three quick release pins.

Parking Jack

Manual parking jack with 5" swivel wheel.

Tires

(2) ST225-75-R15 radial tires on steel wheels.

Options

- Hydraulic parking jack in lieu of manual
- Fluid drive coupler in lieu of standard clutch
- Remote electric throttle for engine
- Remote electric clutch for engine
- 45 degree intake hose flange
- Urethane suction hose in lieu of rubber
- Urethane coated liners for blower housing
- Driver's side (street) pick up

Engine - Option

John Deere 4045TFC03 4-cylinder diesel engine rated at 74HP - Final T4

Radiator Screen

Boxed corrugated radiator screen constructed from perforated steel to increase air flow for better cooling.

Intake Hose

16" x 120" rubber suction hose with steel nozzle.

Exhaust Hose

16" dia. x 48" long rubber exhaust hose.

Hose Boom

Hydraulic hose boom powered by a 12V electric / hydraulic pump.

Trailer

1/4" thick trailer deck with channel members on the ends.

Axles

Single 6,000 lb. Torflex axle with EZ lube hubs and electric brakes with break away actuator.

Fuel Tank

44-gal. polyethylene fuel tank located under the trailer bed.

Lights

LED type DOT trailer lights. One amber LED flasher light at the rear.

Paint

All components are pre-painted with PPG paint. Unit - standard white, Custom paint colors available as options.



*Units may be shown with options.