

Xtreme VAC

by 



LCT600

- Kubota WSG3800 3.8L
4-cylinder gasoline engine
rated 87HP, EPA T2
- 28" suction impeller
 - Hydraulic hose boom
 - 16" dia. x 120" rubber intake hose

The LCT600 has the best suction of any unit in it's class. Contact your local Xtreme Vac dealer to order yours today!

*Standard color is white.

*Units may be shown with options.



Sold and Serviced by:



Call: 1-800-362-0240
Email: sales@mtechcompany.com

Scan using your phone's camera



Sourcewell
Formerly NJPA

Awarded Contract

Contract # 041217-ODB



Specifications

Tow-Behind Debris Collector-Trailer Mounted

Engine - Gas

Kubota WSG3800 3.8L 4-cylinder gasoline engine, rated at 87HP, meets EPA T2 & CARB T3 standards.

Engine Controls

Electronic engine controls with safety shut down.

Drive

Belt driven via a 4-groove Kevlar power band.

PTO

13" clutch assembly with 2.25" PTO shaft and safety engagement system.

Trailer

1/4" thick trailer deck with channel members on ends.

Axles

Single 6,000 lb. Torflex axle with EZ lube hubs. Equipped w/ electric brakes with break-away actuator.

Tires

(2) ST225-75-R15 radial tires on steel wheels.

Options

- 2 or 3-axis hose boom (up/dn, left/rt, in/out)
- Wireless boom controls (multi-axis boom only)
- Rear ride-on seat w/ 7,000lb Torflex axle and wireless belly pack (multi-axis boom only)
- Hydraulic parking jack in lieu of manual
- Fluid drive coupler in lieu of standard clutch
- Remote electric throttle for engine
- Remote electric clutch for engine
- 45 degree intake hose flange
- Urethane suction hose in lieu of rubber
- Urethane coated liners for blower housing
- Driver's side (street) pick up
- 38" Hydraulic curb nozzle
- Hydraulic agitator for curb nozzle
- Rotary self-cleaning radiator screen

Engine - Option

John Deere 4045TFC03 4-cylinder diesel engine rated at 74HP - Final T4

Radiator Screen

Boxed corrugated radiator screen constructed from perforated steel to increase air flow for better cooling.

Intake Hose

16" x 120" rubber suction hose with steel nozzle.

Hose Boom

Hydraulic hose boom powered by 12v electric / hydraulic pump.

Impeller

28" dia. suction impeller with six 3/8" thick T-1 AR steel plate blades. Replaceable 1/4" thick steel liners.

Exhaust Hose

16" dia. x 48" long rubber exhaust hose.

Fuel Tank

44-gallon polyethylene fuel tank.

Pintle Eye

Heavy-duty height adjustable pintle eye with three quick release pins.

Parking Jack

Manual parking jack with 5" swivel castor wheel.

Lights

LED type DOT trailer lights. One amber LED flasher light at the rear.

Paint

All components are pre-painted with PPG paint - Unit - standard white, Engine - Battleship grey Other custom paint colors available as options.



Kubota
Gas
Engine
Option



John Deere
Diesel
Engine
Option